

TO: ALL PAST, PRESENT AND FUTURE NEW PARIS SPEEDWAY LIMITED LATE MODEL CLASS PARTICIPANTS:

THE FOLLOWING LIMITED LATE MODEL CLASS RULES HAVE BEEN ESTABLISHED FOR THE 2022 RACING SEASON. THESE RULES ARE MEANT TO CREATE THE FAIREST, MOST COMPETITIVE ENVIRONMENT POSSIBLE. IT IS OUR GOAL TO GROW THE LIMITED LATE MODEL CLASS TO A MINIMUM "A AND B" FEATURE CLASS ON A WEEKLY BASIS. WE WILL RESERVE THE RIGHT TO MAKE ADJUSTMENTS TO THE WEIGHT AND LEFT SIDE PERCENTAGE REQUIREMENTS IF ANY ONE TYPE OF VEHICLE APPEARS TO BE DISPLAYING A HUGE ADVANTAGE. IF CHANGES ARE NECESSARY WE WILL INFORM YOU A MINIMUM OF 2 WEEKS IN ADVANCE OF THESE CHANGES. WE FULLY UNDERSTAND AND RESPECT YOUR PASSION, HARD WORK AND COMPETITIVE SPIRIT WITHIN EACH OF YOU AND YOUR DESIRE TO HAVE THE FASTEST VEHICLE THAT IS CAPABLE OF WINNING. WE APPRECIATE YOUR COOPERATION AND UNDERSTANDING OF THIS STATEMENT AS WELL AS ALL YOUR EFFORTS TO GROW THIS CLASS

SINCERELY,

TRACY AND CHRIS

NEW PARIS SPEEDWAY



2022 LIMITED LATE MODEL RULES

PLEASE REFER TO RULE BOOK DISCLAIMER, GENERAL AND TRACK RULES

SAFETY:

- 1. All vehicles must have a minimum of a 4 post roll cage with at least 3 bars at the driver's door and a welded or bolted steel plate of $1/8" \times 10" \times 30"$ at the driver's door.
- 2. A full 5 point restraint system is required and may be no older than 3 years old.
- 3. Window nets must be used at all times during participation and may be no older than 3 years old.
- 4. Neck collars or HANS type devices are required for all participants.
- 5. A minimum 2 1/2" lb. fire extinguisher is required to be securely mounted within the driver's reach.
- 6. All Cars must have shut off switch next to the driver's window which can easily be reached from the outside of the car.
- 7. Raceceiver type communication devices required for all classes.

BODY:

- 1. Rear wheel drive cars and trucks only, trucks must have bed covered. No front wheel or 4 wheel drive vehicles are permitted.
- 2. Bodies must be constructed of: Steel, Aluminum or Fiberglass or plastic and MUST conform to the "Body Dimensions" section of this rules document.
- 3. Hood and trunk must be operable and held down with 4 quick release hood type pins.
- 4. Front and rear bumpers must be covered. Pipes may not protrude through bumper covers.
- 5. Full front Lexan windshields required. (no partial windshields will be allowed).
- 6. Driver's side reflection vents and rear windows are permitted provide they are stock appearing and transparent.
- 7. Rear spoilers are allowed with a maximum size of 6 1/2" x 80". Spoilers must be clear, centered and mounted flat.
- 8. Nerf bars must be no larger than 1" in diameter and smoothly capped. A minimum of 4 smooth head bolts must be used for securement. Carriage or equivalent bolts recommended. Bolts must be mounted with the head to the outside of vehicle.

2022 LIMITED LATE MODEL RULES CONTINUED

BODY CONTINUED:

- 9. Batteries are to be covered and securely fastened. No rubber or plumbing straps allowed.
- 10. 22 gallon maximum capacity fuels cells are required. Must be a minimum of 8" from ground.
- 11. Floorboard under driver must be constructed of steel.

BODY DIMENSIONS:

- 1. Minimum wheelbase of 102"
- 2. Maximum track width of 80". Measured with toe boards anywhere on wheels.
- 3. Maximum Body Width of 80". Measured at the widest point of the body.
- 4. Minimum Roof height shall be 47"
- 5. Maximum rear deck height shall be 35". Measured from the ground to the base of the spoiler.
- 6. Maximum front overhang is 46". Measured front the leading edge of the nose to the centerline of the front wheels.
- 7. Maximum rear overhang is 47". Measured from the base of the spoiler to the centerline of the rear wheels.

Chassis:

- 1. Minimum weight of car and driver is 2800lbs. With a maximum of 60.0% left side weight.
- 2. Chassis may have a stock or tubular front clip. Can be OEM or Aftermarket.
- 3. Full tubular chassis vehicles must be a minimum of 2900lbs.
- 4. Lower Control Arms may be stock or tubular style with or without strut rod.
- Upper Control Arms may be tubular steel. ALL BALL JOINTS MUST BE NON-ADJUSTABLE!
- Front Spindles must be Steel or Cast Iron and Stock appearing.
- 7. Coil Springs must be a minimum of 5" in diameter.
- 8. Shocks must permanently enclosed steel shocks and non adjustable. Coil over shocks are not permitted.

 SHOCKS MAY BE CLAIMED BY ANY DRIVER FINISHING ON THE LEAD LAP OF ANY TOP 5 FINISHING CAR

 FOR THAT FEATURE \$150 EACH. NO BUMP STOPS OR COIL BINDING PERMITTED.
- 3 link, 4 link or panhard bar set ups are permitted. No Birdcage Style or Active Rear Suspension allowed.
- 10. Stock Steering box or rack and pinion steering is permitted.

2022 LIMITED LATE MODEL RULES CONTINUED

Chassis continued:

- 11. No chassis adjustments are to be made from the driver's compartment. THIS INCLUDES MANUAL OR ELECTRONIC TRACTION CONTROL DEVICES!
- 12. Minimum frame ground clearance of 4" with driver in the vehicle.
- 13. 4 corner jack bolts are allowed.
- 14. Quick Change differentials are allowed with steel axle tubes.
- 15. Wide 5 hubs are allowed.
- 16. ALL 4 BRAKES MUST BE OPERATIONAL! IN COCKPIT BRAKE BIAS ADJUSTERS ARE PERMITTED.
- 17.All weight must be painted white and be marked with the car number for identification. Weight must be mounted with a minimum of grade 5 bolts or 1/2" grade A threaded rod.
- 18. Always bring extra weight as your interpretation of a rule may differ from the technical directors.

Engine ,Transmission AND Differential:

- 1. Any domestic stock appearing engines will be permitted.
- 2. Maximum engine setback is 4". MEASURED FROM THE #1 SPARK PLUG TO THE BALL JOINT CENTERLINE!
- 3. Engine block and heads must remain cast iron.
- 4. Aluminum intakes are permitted.
- 5. 2 or 4 barrel carburetors are permitted. NO FUEL INJECTION!
- 6. Fuel pumps must be mechanical. NO ELECTRIC FUEL PUMPS!
- 7. No dry sump oil systems permitted.
- 8. Radiators must remain completely underneath hood and not protrude through hood. NO ANTIFREEZE!
- 9. Headers or exhaust manifolds are permitted.
- 10. Exhaust must exit either behind rear of door when run below the floorboard or on the passengers side door towards the rear.
- 11. Quick change type, Bert, Brinn or Falcon Transmissions are allowed.
- 12. Differentials may be GM 10 or 12 Bolt, Ford 9" or quick change. NO LOCKER STYLE DIFFERENTIALS ALLOWED.

2022 LIMITED LATE MODEL RULES CONTINUED

Tires and Wheels:

- 1. Hoosier D800 * Hoosier Tires are Subject to Change based on Availability.
- 2. 8" wide maximum diameter safety wheels only.
- 3. Tires and Wheels must remain inside body.

ALL RULES INTERPRETATIONS AND RULINGS ARE AT THE DISCRETION OF THE TECHNICAL DIRECTOR AND ARE FINAL!

CARS MUST CONFORM TO THE RULES AND BE LEGAL FOR EVERY EVENT! THERE WILL NO LONGER BE ANY 1 WEEK GRACE PERIODS!