



2010 Pure-Stock Rules

www.newparisspeedway.com

REFER TO RULE BOOK DISCLAIMER, GENERAL SAFETY, AND TRACK RULES

1. BODY AND FRAME

- A. NO STATION WAGONS, CONVERTIBLES, OR FRONT WHEEL DRIVES. NO UNIBODIES, CAMARO, MUSTANGS, ETC
- B. MINIMUM WHEELBASE 108"
- C. BODY SHEET METAL MUST REMAIN STOCK.
- D. COCKPITS MUST REMAIN OPEN.
- E. FRONT AND REAR FIREWALL TO REMAIN INTACT WITH STOCK FLOORPAN ANY REMOVAL MUST ADD 200 LBS
- F. HOOD AND TRUNK LID MUST BE PINNED, NO BOLTING DOWN
- G. DOORS TO BE WELDED, CHAINED, OR BOLTED.
- H. ALL CHROME AND GLASS REMOVED.
- I. DOOR PANELS, CARPET, HEADLINERS, ETC. TO BE REMOVED.
- J. ALL DRIVERS MUST USE APPROVED 5 POINT SAFETY HARNESS BELTS, APPROVED RACING HELMETS, AND MUST WEAR APPROVED FIRESUIT AT ALL TIMES ON THE TRACK. WINDOW NETS ARE REQUIRED.
- K. FIRE EXTINGUISHER, MINIMUM 2.5 LBS. TO BE MOUNTED SECURELY IN DRIVERS REACH.
- L. NO SPOILERS.
- M. FRONT AND REAR STOCK BUMPERS ONLY, MUST BE STRAPPED, BOLTED, OR CHAINED.
- N. NO MIRRORS OR RADIOS.
- O. GAS TANKS MUST BE SECURELY FASTENED. FUEL CELLS OK
- P. FRONT WINDSHIELD MAY BE REPLACED IF NECESSARY. (LEXAN IS ACCEPTABLE) WINDSHIELD PROTECTION BARS MAY ALSO BE USED.

We make every attempt to display correct and current information. This site is privately owned and operated. We are not responsible for any misrepresentations or inaccurate information. All race results and point standings are unofficial. Contact New Paris Speedway with all track or race issues. Contact the webmaster directly for all web site related matters; advertising, comments, suggestions, etc.



- Q. ALL SUSPENSION COMPONENTS MUST REMAIN STOCK O.E.M. PARTS, SCREW JACKS ALLOWED ON REAR ONLY.
- R. MINIMUM WEIGHT 3200 LBS.
- S. BATTERIES MAY BE MOUNTED IN STOCK LOCATION OR ANY OTHER SAFE POSITION. IF IN DRIVERS COMPARTMENT, IT MUST BE MOUNTED INSIDE A SAFE AND SECURELY MOUNTED BOX. THE BATTERY MUST BE COVERED.
- T. TOTAL LEFT SIDE WEIGHT NOT TO EXCEED 57%

2. ENGINE AND DRIVETRAIN

- A. ENGINE MUST BE STOCK FOR MAKE AND MODEL.
- B. STOCK CAST IRON INTAKE AND EXHAUST MANIFOLDS, CENTER DUMPS OK
- C. ENGINE MUST REMAIN IN STOCK MOUNTS. ALL PARTS MUST BE O.E.M.
- D. HOLLEY 4412 CARBURETOR OR STOCK CARBURETOR OK. ALL CARBURETORS MUST HAVE THE FULL CHOKE BUTTERFLY INTACT AND WIRED OPEN.
- E. STOCK STYLE H.E.I. IGNITION ONLY. NO MSD STYLE IGNITIONS.
- F. AUTOMATIC TRANSMISSIONS ONLY. MUST HAVE WORKING TORQUE CONVERTER, REVERSE, AND CAR MUST IDLE IN GEAR. OR AN OEM MANUAL TRANSMISSION AND MINIMUM 7.25 CLUTCH WITH A 200lb PENTALTY.
- G. POSI-TRAC, LIMITED SLIP, WELDED, OR LOCKED DIFFERENTIALS WILL BE ALLOWED. 9" FORD REAR-ENDS IN FORDS ONLY
- H. BRAKES MUST WORK ON ALL 4 WHEELS WITH NO BRAKE BIAS DEVICES ALLOWED. NO DISC BRAKES ON REAR.
- I. ONE GALLON RADIATOR OVER-FLOW CATCH CAN IS MANDATORY WITH OVER-FLOW HOLES TO EXIT ON WINDSHIELD.
- J. USE OF ANTI-FREEZE IS NOT ALLOWED.

3. TIRES AND WHEELS

- A. HOOSIER 790'S OR ANY D.O.T. 70 SERIES STREET LEGAL 7" MAX TREAD WITH TIRES.
- B. MAX 8" WIDE STEEL SAFETY WHEELS ONLY. 1" LUG NUTS HIGHLY RECOMMENDED.

We make every attempt to display correct and current information. This site is privately owned and operated. We are not responsible for any misrepresentations or inaccurate information. All race results and point standings are unofficial. Contact New Paris Speedway with all track or race issues. Contact the webmaster directly for all web site related matters; advertising, comments, suggestions, etc.