



## 2012 Pure Stock Rules

REFER TO RULE BOOK DISCLAIMER, GENERAL SAFETY, AND TRACK RULES

### I. BODY AND FRAME

- A. No station wagons, convertibles, or front wheel drives.
- B. Minimum wheel base 108"
- C. Body sheet metal must remain stock appearing.
- D. Cockpits must remain open.
- E. Front and rear firewall to remain intact with stock floor plan. Any removal must add 200 lbs.
- F. Hood and trunk lid must be pinned, NO bolting down.
- G. Doors to be welded, chained, or bolted.
- H. All chrome and glass removed.
- I. Door panels, carpet, headliners, etc. to be removed.
- J. All drivers must use 5 point safety harness belts, approved racing helmets, and must wear approved firesuit at all times on the racetrack. Window nets are required.
- K. Fire extinguisher, minimum 2.5 lbs, to be mounted securely in driver reach.
- L. NO spoilers.
- M. Front and rear stock bumpers only. Must be strapped, bolted, or chained. Tubular bumpers must be covered.
- N. NO mirrors or radios.
- O. Gas tanks must be securely fastened. Fuel cells are allowed.
- P. Front windshield may be replaced if necessary (Lexan is acceptable). Windshield protection bars may also be used.
- Q. Shocks must be factory OEM shocks.
- R. All suspension components must remain stock OEM parts. Screw jacks allowed on rear ONLY.
- S. Minimum weight 3200 lbs.
- T. Batteries may be mounted in stock location or any other safe position. If in driver's compartment, it must be mounted inside a safe and securely mounted box. The battery must be covered.

- U. Total left side weight NOT to exceed 57%.

## **II. ENGINE**

- A. Engine must be stock for make and model and in stock position.
- B. Stock cast iron intake and exhaust manifolds. Center dumps are allowed.
- C. Engine must remain in stock mounts. All parts must be OEM.
- D. Holley 4412 carburetor or stock carburetor is allowed. All carburetors must have the full choke butterfly intact and wired open.
- E. Stock style HEI ignition ONLY. NO MSD style ignitions.
- F. Automatic transmission only. Must have working torque converter, reverse, and car must idle in gear (or an OEM manual transmission and minimum 7.25 clutch with a 200 lbs penalty).
- G. Posi-trac, limited slip, welded or locked differentials will be allowed. 9" Ford rear-ends in Fords ONLY.
- H. Brakes must work on all 4 wheels. NO brake bias devices allowed.
- I. One gallon radiator over-flow catch can is mandatory with over-flow holes to exit on windshield.
- J. Use of antifreeze is NOT allowed.

## **III. TIRES AND WHEELS**

- A. Hoosier 790's or any D.O.T. 70 series street legal 7" max treads with tires.
- B. Max 8" wide steel safety wheels ONLY. 1" lug nuts highly recommended.

**\*\*BRING WEIGHT, our interpretation of a rule may be different than yours!\*\***