



2016 Late Model Sportsman Rules

REFER TO RULE BOOK DISCLAIMER, GENERAL SAFETY, AND TRACK RULES

Stock or Manufactured Front Clip with stock type lower A-frames. 2775 lbs.

Any Front Clip utilizing strut type suspension and/or rack & pinion steering 2800 lbs.

I. SUSPENSION

- A. 5" OR 2 1/2" coil springs front & rear allowed.
- B. Quick change rear ends allowed.
- C. Maximum 8" wide steel wheels only.
- D. Maximum 60.0% left side weight at all times.
- E. Maximum track width 80"
- F. Track width 78" or less, deduct 50 lbs.
- G. Minimum weight with adds & deductions 2750 lbs.
- H. Shocks: Gas shocks or shocks that list over \$300.00 may be used with a minimum weight of 2900 lbs. and 58% left side weight.
- I. Tires: To be announced
- J. Any birdcage style of any kind. (3 or 4 link). And/or 5th coil-Lift bar suspension. Any part of rear trailing arm mounting that freely rotate around rear end, add 50lbs

II. ENGINE

- A. Maximum engine setback 4" from a centerline between the upper ball joints to the center of the farthest forward cylinder.
- B. 2" engine setback, deduct 50 lbs.
- C. Center of crankshaft must have a minimum of 10" ground clearance.
- D. Aluminum heads, add 50 lbs.
- E. Any engines utilizing an external oil pump, add 50 lbs.
- F. Cast iron intake & exhaust, deduct 50 lbs.

III. BODY

- A. Stock appearing bodies may be aftermarket or OEM. Body should be ABC or similar stock appearing body. No outlaw or squared sided bodies. Steel, fiberglass, or plastic panels ok. Standard 5-star or ARP pavement short track noses, roof and rear bumper covers must be used. Fenders, quarter panels and doors may be fabricated but must be similar in appearance.
- B. Minimum 4" ground clearance on all parts of body.
- C. Side windows may go no further back than 12" from the A-post door corner and must go up at a 90 degree angle from the door.
- D. Maximum front overhang measured from the centerline of the front wheels to the leading edge of the nose is 46".
- E. Maximum length allowed for the nose measured from the bottom leading edge at center up to the hood seam is 20"
- F. Maximum rear overhang measured from the centerline of rear wheels to the base of rear spoiler is 47".
- G. Minimum roof height measured 10" from the windshield is 47".
- H. Maximum rear quarter panel is 34.5".
- I. Maximum body width at any point is 79.5".
- J. Rear deck should remain relatively flat, side to side, and front to rear.
- K. Spoilers must be centered on car and may not exceed 390 square inches. (ex. 6 1/2" x 60" or 6" x 65")
- L. Rub rails may only be used if they are polycarbonate.

All cars must meet all Safety and Track rules.