



## 2018 Mini Stock Rules

REFER TO RULE BOOK DISCLAIMER, GENERAL SAFETY, AND TRACK RULES

### BODY AND FRAME

**Uni-Bodies that have been tied together, and/or fabrications that enhanced the performance of the chassis must add 100 lbs.**

- A. Body must be subcompact, 4 cylinder model (NO Firebirds, Camaros, Fairmont's, etc.). Station wagons and pickups are allowed. No convertibles or 4 wheel drives. No rear engine or mid-engine models.
- B. V6 or 4 cylinder front wheel drives allowed. Front wheel driver will be allowed 2" wider and 100 lbs. lighter.
- C. All suspension must be kept stock. No modifications of any kind. Officials' discretion is FINAL.
- D. Body must be sheet metal or aluminum and fully stock appearing. Roof, windshield post and cowl must remain stock. Pickups must enclose bed. Stock appearing after-market noses are allowed. Maximum 70" Body width. Minimum 50" roof height. No more than a 2" rake on body and roof.
- E. Bumper Covers must cover complete bumpers. No steel pipe to protrude through covers.
- F. Doors must be welded or bolted shut.
- G. With the exception of windshield, all glass must be removed. NO rear windows allowed.
- H. Safety constructed 4 post cage with minimum of three bars on driver's side and one bar on passenger side
- I. Must have firewall between driver and engine, and driver and fuel tank.
- J. Fenders may be trimmed for tire clearance only.
- K. NO holes in hood for air cleaner.
- L. Hood and trunk must be pinned. NO bolting down.
- M. 4" X 60" rear spoilers are allowed.
- N. Stock type A-arms, struts, and ball joints ONLY. **Any strut or shock that is available at any local part house that list for under \$200 will be allowed.**
- O. Cars must remain original track width as manufactured. Not to exceed 72" outside to outside. Front wheel drive cars not to exceed 74" outside to outside.
- P. Deduct 50 lbs. with 70" track width and 6" wheels.

- Q. Steering components may be aftermarket except steering box.
- R. Aftermarket brake pedal assemblies are allowed..
- S. Minimum weight of car with driver, AFTER RACE, is 2400 lbs. NO bolt in ballast weight. Front wheel driver minimum weight 6-cylinder 2300 lbs. 4-cylinder 2200 lbs.
- T. Screw jacks allowed.
- U. NO coil-over type adjusters.
- V. Must have 4 wheel operating brakes. Must be factory stock brake system.
- W. NO quick change type or trick automatic transmissions or rear ends. No 4 wheel drives.

## II. ENGINE

- A. Engine must be 4 cylinder, carburetor fed and remain in stock location
- B. Single carburetors only, not to exceed 2 barrels. Any Holley 4412 carburetor will be allowed.
- C. Heads must be of stock manufacturer's original cast iron. NO aluminum or aftermarkets allowed. **Only if original engine has aluminum head and is not a Ford will be allowed. Aluminum Intakes are allowed.**
- D. Fuel injection allowed on front wheel drive cars ONLY.
- E. Exhaust must be single and completely sealed and must go past doors. Headers will be allowed.
- F. Aftermarket Ignition systems will be allowed. **Must add 50 Lbs.**
- G. NO racing clutches. A camera will be used to check. Must remove clutch at track after race if in question.
- H. A 2" hole must be cut in bell housing to check for stock clutches. Must be visible.
- I. Fuel cells are strongly recommended. Fuel tank must be safely secure with 4 steel straps. If moving fuel tank into hatchback area or pickup, bed must have firewall between driver. Fuel cells must be enclosed in steel can.
- J. Steel lines or braided hose must be used as fuel line from fuel tank to carburetor. NO fuel line in cockpit area.

## III. TIRES AND WHEELS

- A. Any 65, 70, 75, or 80 series D.O.T. radial tire, 195 or smaller. \$75 claim rule on tires.
- B. Maximum 7" wide steel safety wheels.
- C. 15" tires and wheels allowed.

## IV. MISCELLANEOUS

- A. Car and driver must meet ALL safety rules or will not race. Any deviations of these rules are left to the discretion of the officials and their decision is FINAL.

**\*\*BRING WEIGHT, our interpretation of a rule may be different than yours!\*\***