



**TO: ALL PAST, PRESENT AND FUTURE NEW PARIS SPEEDWAY STREET STOCK
CLASS PARTICIPANTS:**

THE FOLLOWING STREET STOCK CLASS RULES HAVE BEEN ESTABLISHED FOR THE 2021 RACING SEASON. THESE RULES ARE MEANT TO CREATE THE FAIREST, MOST COMPETITIVE ENVIRONMENT POSSIBLE. IT IS OUR GOAL TO GROW THE STREET STOCK CLASS TO A MINIMUM "A AND B" FEATURE CLASS ON A WEEKLY BASIS. WE WILL RESERVE THE RIGHT TO MAKE ADJUSTMENTS TO THE RULES IN THE INTEREST OF SAFETY OR COMPETITIVENESS. IF CHANGES ARE NECESSARY WE WILL INFORM YOU A MINIMUM OF 2 WEEKS IN ADVANCE OF THESE CHANGES. WE FULLY UNDERSTAND AND RESPECT YOUR PASSION, HARD WORK AND COMPETITIVE SPIRIT WITHIN EACH OF YOU AND YOUR DESIRE TO HAVE THE FASTEST VEHICLE THAT IS CAPABLE OF WINNING. WE APPRECIATE YOUR COOPERATION AND UNDERSTANDING OF THIS STATEMENT AS WELL AS ALL YOUR EFFORTS TO GROW THIS, THE PREMIER WEEKLY CLASS AT NEW PARIS SPEEDWAY.

SINCERELY,

TRACY AND CHRIS

NEW PARIS SPEEDWAY



2021 STREET STOCK RULES

PLEASE REFER TO RULE BOOK DISCLAIMER, GENERAL AND TRACK RULES

SAFETY:

1. *All vehicles must have a minimum of a 4 post roll cage with at least 3 bars at the driver's door and a welded or bolted steel plate of 1/8" x 10" x 30" at the driver's door.*
2. *A full 5 point restraint system is required and may be no older than 3 years old.*
3. *Window nets must be used at all times during participation and may be no older than 3 years old.*
4. *Neck collars or HANS type devices are required for all participants.*
5. *A minimum 2 1/2" lb. fire extinguisher is required to be securely mounted within the driver's reach.*
6. *All Cars must have shut off switch next to the driver's window which can easily be reached from the outside of the car.*
7. *Raceceiver type communication devices required for all classes.*

BASE WEIGHT:

1. *Minimum weight of car and helmeted driver is 3100lbs. With a maximum of 59% left side weight for full frame pocket to pocket with **steel body**. (Steel Doors, Fenders and quarter panels)*
2. *Minimum weight of car and helmeted driver is 3200lbs. With a maximum of 59% left side weight for full frame pocket to pocket with **template or aluminum body**.*

Chassis:

1. *Full stock frame pocket to pocket only. **NO FABRICATED CHASSIS OF ANY KIND ARE PERMITTED!***
2. *Minimum wheelbase is 102".*
3. *Minimum frame ground clearance of 5" with driver in the vehicle.*
4. *Maximum track width of 78". **Measured with toe boards anywhere on wheels.***
5. *Suspension Mounts must be stock and in the stock location. **Underslung Sway Bars permitted.***
6. *Stock 4 Link rear suspension in stock location only. **3 LINK REAR SUSPENSION OR PANHARD BARS ARE NOT PERMITTED!***
7. *GM 10 or 12 bolt and ford 9" rear ends are permissible but must have steel axle tubes. **NO LIMITED SLIP TYPE REAR ENDS!***

2021 STREET STOCK RULES CONTINUED

Chassis Continued:

8. 4 corner jack bolts are allowed.
9. Adjustable Heim Joints are permitted on Rear Trailing Arms.
10. All Front Suspension Components must be stock for the make and model of the vehicle. **AFTERMARKET UPPER A-ARMS ARE PERMITTED WITH NON-ADJUSTABLE BALL JOINTS! AFTERMARKET, STOCK APPEARING SPINDLES ARE ALSO PERMITTED.**
11. Minimum Spring diameter is 5".
12. Stock Steering box and conventional steering components only. No rack and pinion steering.
13. Shocks must be Steel , non-adjustable style shocks and Nationally advertised. Shock list price must not exceed \$145.00 per shock.
14. **NO BUMP STOPS OR COIL BINDING WILL BE PERMITTED!**
15. **FOUR WHEEL DISC BRAKES ARE PERMITTED. CALIPERS MUST BE SINGLE PISTON STEEL OR ALUMINUM.**
16. **ALL 4 BRAKES MUST BE OPERATIONAL! IN COCKPIT BRAKE BIAS ADJUSTERS ARE PERMITTED.**
17. Fuel Cell must be mounted above the rear end centerline with a minimum of 8" ground clearance.
18. Aftermarket gas pedal and brake pedals are permissible.
19. **TRACTION CONTROL DEVICES OF ANY KIND ARE STRICTLY PROHIBITED!**

BODY:

1. Rear wheel drive cars and trucks only, trucks must have bed covered. **No front wheel or 4 wheel drive vehicles are permitted.**
2. Stock appearing steel bodies must weigh a minimum of 3100 Lbs. **(See Base Weight Rule)**
3. Any template appearing body must weigh a minimum of 3200 Lbs. **(See Base Weight Rule)**
4. Nose and Tailpieces must be stock appearing. 5 Star plastic type are allowed.
5. Minimum Roof Height of 47". **MEASURED AT ANY POINT!**
6. Hood and trunk must be operable and held down with 4 quick release hood type pins.
7. Full front Lexan windshields required. **(no partial windshields will be allowed).**
8. Rear spoilers are allowed with a maximum size of 6 1/2 " x 60". Spoilers must be clear, centered and mounted flat.
9. Nerf bars (RUB RAILS) must be no larger than 1" in diameter and smoothly capped. A minimum of 4 smooth head bolts must be used for securement. Carriage or equivalent bolts recommended. Bolts must be mounted with the head to the outside of vehicle.

2021 STREET STOCK RULES CONTINUED

BODY CONTINUED:

10. Batteries are to be covered and securely fastened. **No rubber or plumbing straps allowed.**
11. 22 gallon maximum capacity fuel cells are required. Must be a minimum of 8" from ground.
12. Floorboard under driver must be stock or constructed of 1/8" minimum thickness steel.
13. **COCKPIT LEDGES ARE PROHIBITED!**
14. Racing type seats are mandatory. **NO FIBERGLASS SEATS!**
15. **NO MIRRORS OR RADIOS!**
16. Hood cowls may be used but air cleaners must not be exposed.

Engine and Transmission:

1. Any domestic stock appearing engines will be permitted.
2. Engine block and heads must remain cast iron.
3. Aluminum intakes are permitted.
4. 2 or 4 barrel carburetors are permitted. **NO FUEL INJECTION!**
5. Fuel pumps must be mechanical. **NO ELECTRIC FUEL PUMPS!**
6. No dry sump oil systems permitted.
7. Maximum engine setback is 2". **MEASURED FROM THE #1 SPARK PLUG TO THE BALL JOINT CENTERLINE!**
8. Stock HEI or MSD ignitions are permitted.
9. Radiators must remain completely underneath hood and not protrude through hood. **NO ANTIFREEZE!**
10. Headers or exhaust manifolds are permitted.
11. Exhaust must exit either behind rear of door when run below the floorboard or on the passengers side door towards the rear.
12. Transmissions: Automatic with 10.5" convertor or Manual with 11" or Mini Clutch are permitted.
13. Aluminum Flywheels are permitted.
14. Direct Drive or Aftermarket Transmissions are prohibited.
15. Transmission Coolers in Cockpit are prohibited.
16. Driveshaft Safety Loops are mandatory.

2021 STREET STOCK RULES CONTINUED

Tires and Wheels:

- 1. Hoosier 800 tires only.***
- 2. 8" wide maximum diameter safety wheels only.***
- 3. Tires and Wheels must remain inside body.***

ALL RULES INTERPRETATIONS AND RULINGS ARE AT THE DISCRETION OF THE TECHNICAL DIRECTOR AND ARE FINAL!

ALL ADDITIONAL WEIGHT MUST BE PAINTED WHITE AND HAVE YOUR VEHICLE NUMBER ON IT. WEIGHTS MUST BE FASTENED WITH A MINIMUM OF 1/2" THREADED STEEL ROD AND NOT PROTRUDE BELOW THE FRAME.

CARS MUST CONFORM TO THE RULES AND BE LEGAL FOR EVERY EVENT! THERE WILL NO LONGER BE ANY 1 WEEK GRACE PERIODS!